

## LTM8002HY#PBF

Data Sheet

40VIN, 2.5A Silent Switcher µModule Regulator

Manufacturers <u>Analog Devices, Inc</u>


Package/Case 49-Lead BGA (6.25mm x 6.25mm x 2.22mm)

Product Type Power Management ICs

**RoHS** 

Lifecycle

Please submit RFQ for LTM8002HY#PBF or Email to us: sales@ovaga.com We will contact you in 12 hours.



Images are for reference only

<u>RFO</u>

## **General Description**

The LTM8002 is a 40VIN, 2.5A step-down  $\mu$ Module® (power module) regulator. Included in the package are the switching controller, power switches, inductor, and all support components. Operating over an input voltage range of 3.4V to 40V, the LTM8002 supports an output voltage range of 0.97V to 18V and a switching frequency range of 200kHz to 3MHz, each set by a single resistor. Only the input and output filter capacitors are needed to finish the design.

The low profile package enables utilization of unused space on the bottom of PC boards for high density point of load regulation. The LTM8002 is packaged in a thermally enhanced, compact over-molded ball grid array (BGA) package suitable for automated assembly by standard surface mount equipment. The LTM8002 is available with SnPb or RoHS compliant terminal finish.

## **Features**

Complete Step-Down Switch Mode Power Supply

Low Noise Silent Switcher® Architecture

Wide Temperature Range: -40°C to 150°C (H-Grade)

2.8A Continuous for 5VOUT, 12VIN, 2MHz at 105°C (H-Grade)

Selectable Switching Frequency: 200kHz to 3MHz

External Synchronization

Low Quiescent Current: 25µA (5VOUT)

Tiny, Low Profile 6.25mm × 6.25mm × 2.22mmBGA Package

## **Related Products**



**LT3763EFE** Analog Devices, Inc TSSOP28




**LTC4417IUF** 



Analog Devices, Inc QFN-24



LTC1966CMS8#PBF





LTM8045EY#PBF

Analog Devices, Inc BGA40



LT1038CK

Analog Devices, Inc TO-3



LTC3440EMS

Analog Devices, Inc MSOP10



LTC2990IMS#PBF

Analog Devices, Inc 10MSOP



LT4295IUFD#PBF

Analog Devices, Inc 28-WFQFN