

OP177FPZ

Data Sheet

Operational Amplifier, Single, 1 Amplifier, 600 kHz, 0.3 V/µs, \pm 3V to \pm 18V, DIP, 8 Pins

| Manufacturers | Analog Devices, Inc | |
|---------------|---------------------|-------------------------------|
| Package/Case | PDIP-8 | |
| Product Type | Amplifier ICs | 411. |
| RoHS | Pb-free Halide free | |
| Lifecycle | | Images are for reference only |
| | | |

Please submit RFQ for OP177FPZ or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

The OP177 features one of the highest precision performance of any operational amplifier currently available. Offset voltage of the OP177 is only 25 μ V maximum at room temperature. The ultralow VOS of the OP177 combines with the exceptional offset voltaged rift (TCVOS) of 0.3 μ V/°C maximum to eliminate the need for external VOS adjustment and increases system accuracy overtemperature.

The OP177 open-loop gain of 12 V/ μ V is maintained over the full \pm 10 V output range. CMRR of 130 dB minimum, PSRR of 120 dBminimum, and maximum supply current of 2 mA are just a fewexamples of the excellent performance of this operational amplifier. The combination of outstanding specifications of the OP177 ensures accurate performance in high closed-loop gainapplications.

This low noise, bipolar input operational amplifier is also a costeffective alternative to chopper-stabilized amplifiers. The OP177provides choppertype performance without the usual problems of high noise, low frequency chopper spikes, large physical size, limited common-mode input voltage range, and bulky external storage capacitors.

The OP177 is offered in the -40° C to $+85^{\circ}$ C extended industrial temperature ranges. This product is available in 8-lead PDIP, as well as the space saving 8-lead SOIC.

Features

Ultralow offset>

Outstanding offset voltage drift 0.3 $\mu V/^{\!\circ}C$ maximum

Excellent open-loop gain and gain linearity

 $12 \text{ V/}\mu\text{V}$ typical

CMRR: 130 dB minimum

PSRR: 115 dB minimum

Low supply current 2.0 mA maximum

Fits industry-standard precision operational amplifier sockets

Related Products



OP213F Analog Devices, Inc SMD/DIP-8/SOP-8



OP27GP Analog Devices, Inc PDIP-8



OP462GSZ

Analog Devices, Inc SOIC-14



OP467GPZ Analog Devices, Inc PDIP-14



<u>OP42AZ</u>

Analog Devices, Inc CDIP-8





Analog Devices, Inc SOIC-8

OP2177ARM

Analog Devices, Inc MSOP8

<u>OP400GPZ</u>

Analog Devices, Inc PDIP-14


