

PIC24HJ12GP201-I/SO

Data Sheet

PIC/DSPIC Microcontroller, PIC24 Family PIC24HJ GP Series Microcontrollers, PIC24, 16bit, 80 MHz

Manufacturers	Microchip Technology, Inc	
Package/Case	SOIC-18	STREET,
Product Type	Embedded Processors & Controllers	
RoHS	Rohs	
Lifecycle		Images are for reference only
Please submit RFQ for PIC24HJ12GP201-I/SO or Email to us: sales@ovaga.com We will contact you in 12 hours.		

General Description

The PIC24H 16-bit device family employs a powerful 16-bitarchitecture, ideal for applications that rely on high-speed, repetitivecomputations, as well as control. The devices are pin compatible with thedsPIC33F family of devices, and share a very high degree of compatibility with the dsPIC30F family devices. This allows seamless migration options from/toPIC24F, dsPIC30F and dsPIC33F devices.

Features

Operating Range

Up to 40 MIPS operation

Industrial temperature range (-40°C to +85°C)

Extended temperature range (-40°C to +125°C)

High Efficiency PIC24H core

Modified Harvard architecture

C compiler optimized instruction set

16-bit-wide data path, 24-bit-wide instructions

Linear program memory addressing up to 4M instruction words

Linear data memory addressing up to 64 Kbytes

71 base instructions, mostly one word/one cycle Sixteen 16-bit general purpose registers Flexible and powerful addressing modes 16 x 16 multiply operations 32/16 and 16/16 divide operations Up to ± 16 -bit shifts for up to 40-bit data Interrupt Controller 5-cycle latency Up to 21 available interrupt sources Up to three external interrupts Seven programmable priority levels Four processor exceptions Digital I/O Peripheral Pin Select Functionality Up to 21 programmable digital I/O pins Wake-up/Interrupt-on-Change for up to 21 pins Output pins can drive from 3.0V to 3.6V Up to 5V output with open drain configurations on 5V tolerant pins 4 mA sink on all I/O pins System Management Flexible clock options: - External, crystal, resonator, internal RC, fully integrated Phase-Locked Loop (PLL) and extremely low-jitter PLL Power-up Timer Oscillator Start-up Timer/Stabilizer Watchdog Timer with its own RC oscillator Fail-Safe Clock Monitor (FSCM) Reset by multiple sources Power Management

On-chip 2.5V voltage regulator

Switch between clock sources in real time

Idle, Sleep, and Doze modes with fast wake-up

Timers/Capture/Compare

Timer/Counters, up to three 16-bit timers: - Can pair up to make one 32-bit timer, one timer runs as Real-Time Clock with external 32.768 kHz oscillator and programmable prescaler

Input Capture (up to four channels): - Capture on up, down, or both edges, 16-bit capture input functions and 4-deep FIFO on each capture

Output Compare (up to two channels): - Single or Dual 16-bit Compare mode, 16-bit Glitchless PWM Mode

Communication Modules

4-wire SPI with framing supports I/O interface to simple codecs, supports 8-bit and 16-bit data and all serial clock formats and sampling modes

I2CTM with Full Multi-Master Slave mode support, 7-bit and 10-bit addressing, bus collision detection and arbitration, integrated signal conditioning, slave address masking

UART with LIN bus support, IrDA® encoding and decoding in hardware, High-Speed Baud Mode, Hardware Flow Control with CTS and RTS

Analog-to-Digital Converters (ADCs)

10-bit, 1.1 Msps or 12-bit, 500 Ksps conversion

Two and four simultaneous samples (10-bit ADC)

Up to 10 input channels with auto-scanning

Conversion start can be manual or synchronized with one of four trigger sources

Conversion possible in Sleep mode

Packaging

18-pin PDIP/SOIC

28-pin SPDIP/SOIC/QFN/SSOP

Related Products



PIC24F16KA101-J/SS Microchip Technology, Inc SSOP-20



PIC16F1936-I/SS

Microchip Technology, Inc SSOP-28



PIC16F1938-I/SP

Microchip Technology, Inc PDIP-28



PIC18F23K22-I/SP

Microchip Technology, Inc SPDIP-28



PIC18F6520-I/PT

Microchip Technology, Inc TQFP-64



PIC18F2620-I/SO Microchip Technology, Inc SOIC-28



PIC18F2620-I/SP

Microchip Technology, Inc SPDIP-28

PIC18F97J60T-I/PT

Microchip Technology, Inc TQFP-100