🔉 ovaga

MAX14753EUE+

Data Sheet

8-Channel/Dual 4-Channel 72V Analog Mux; Package: TSSOP, 16 pin ; Temperature Range: -40°C to +85°C

Manufacturers	Analog Devices, Inc
Package/Case	TSSOP16
Product Type	Interface ICs
RoHS	Rohs
Lifecycle	



Images are for reference only

Please submit RFQ for MAX14753EUE+ or Email to us: sales@ovaga.com We will contact you in 12 hours.

<u>RFQ</u>

General Description

MAX14753EUE+ is a high-voltage, low-power, current-limited switch with an integrated power MOSFET, designed for use in applications where the load needs to be protected from overcurrent or short-circuit conditions. It is manufactured by Maxim Integrated, and is available in a 16-pin TSSOP package.

Application

Features

Wide input voltage range: 4.5V to 28V	Industrial and automation equipment
Low quiescent current: 7µA (typical)	Battery-powered devices
Adjustable current limit: up to 2.5A (typical)	Portable medical equipment
Overvoltage protection: up to 32V (typical)	Electronic point-of-sale terminals
Thermal shutdown protection	Network equipment and servers
Fault indication output	LED lighting systems
Soft-start feature to limit inrush current	Motor control



Related Products



Analog Devices, Inc TSSOP-16

MAX3232EEUE



MAX202CSE

Analog Devices, Inc SOP-16



2) dillaga

<u>MAX4544EUT+T</u>

Analog Devices, Inc SOT-23-6

MAX485ECPA

Analog Devices, Inc DIP-8



MAX3221EEUE

Analog Devices, Inc TSSOP-16



MAX3323EEUE

Analog Devices, Inc TSSOP-16



MAX490MJA

Analog Devices, Inc CDIP-8



MAX3232EUE

Analog Devices, Inc TSSOP-16