

TinyLogic UHS Triple Buffer with Schmitt Trigger Inputs; Package: US8; No of Pins: 8;
 Container: Tape & Reel, Buffers & Line Drivers Triple Buffer with Schmitt Trigger

Manufacturers	ON Semiconductor, LLC
Package/Case	US8-8
Product Type	Logic ICs
RoHS	Rohs
Lifecycle	



Images are for reference only

Please submit RFQ for NC7NZ17K8X or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.



General Description

The NC7NZ17 is a triple buffer with Schmitt trigger inputs from Fairchild's Ultra High Speed Series of TinyLogic® in the US8 package. The device is fabricated with advanced CMOS technology to achieve ultra high speed with high output drive while maintaining low static power dissipation over a very broad VCC operating range. The device is specified to operate over the 1.65V to 5.5V VCC range. The inputs and outputs are high impedance when VCC is 0V. Inputs tolerate voltages up to 7V independent of VCC operating voltage. Schmitt trigger inputs typically achieve 1V hysteresis between the positive going and negative going input threshold voltage at 5V VCC.

Application

ONSEMI

Related Products



[NC7SZ18P6X](#)

ON Semiconductor, LLC
 SC-70-6



[NC7SV04P5X](#)

ON Semiconductor, LLC
 SC-70-5



[NC7SV32P5X](#)

ON Semiconductor, LLC
 SC-70



[NC7SV08P5X](#)

ON Semiconductor, LLC
 SC-70



[NC7S32M5X](#)

ON Semiconductor, LLC
SOT-23



[NC7SV157P6X](#)

ON Semiconductor, LLC
SC-70-6



[NC7WZ08K8X](#)

ON Semiconductor, LLC
VSOP-8



[NC7SZ00P5X](#)

ON Semiconductor, LLC
SC-70