

TC4427AEOA713

Data Sheet

<u>RFO</u>

Driver 1.5A 2-OUT Low Side Non-Inv Automotive 8-Pin SOIC N T/R

Manufacturers	Microchip Technology, Inc	E F F
Package/Case	SOIC-8	
Product Type	Power Management ICs	EEEE
RoHS	Rohs	
Lifecycle		Images are for reference only

Please submit RFQ for TC4427AEOA713 or Email to us: sales@ovaga.com We will contact you in 12 hours.

General Description

The TC4426A/4427A/4428A are improved versions of the earlier TC426/427/428 family of buffer/drivers (with which they are pin compatible). They will not latch up under any conditions within their power and voltage ratings. They are not subject to damage when up to 5V of noise spiking (of either polarity) occurs on the ground pin. They can accept, without damage or logic upset, up to 500mA of reverse current (of either polarity) being forced back into their outputs. All terminals are fully protected against up to 4kV of electrostatic discharge. As MOSFET drivers, the TC4426A/4427A/4428A can easily switch 1000pF gate capacitances in under 30nsec, and provide low enough impedances in both the ON and OFF states to ensure the MOSFETs intended state will not be affected, even by large transients.

Features

- Wide Operating Range: 4.5V to 18V
- High Capacitive Load Drive Capability: 1000pF in 25nsec
- Short Delay Times: <30nsec Typ.
- Matched Rise, Fall and Delay Times
- Low Supply Current
- With Logic '1' Input: 1mA
- With Logic '0' Input: 100µA
- Low Output Impedance: 7Ω Typ.
- Latch-Up Protected: Will Withstand >0.5A Reverse Current
- Input Will Withstand Negative Inputs Up to 5V
- ESD Protected: 4kV
- Pinouts Same as TC426/27/28

Related Products



TC7662BEOA

Microchip Technology, Inc SOIC-8



TC4428EOA Microchip Technology, Inc

SOIC-8

TC4426EPA



Microchip Technology, Inc PDIP-8



TC1015-1.8VCT713 Microchip Technology, Inc SOT-23-5








Microchip Technology, Inc

TC7107ACKW

TC4420EOA

SOIC-8



TC7662BCOA713

Microchip Technology, Inc SOIC-8