

ADG609BRUZ

Data Sheet

LC2MOS, \pm 5 V, 4-Channel High Performance Analog Multiplexer; Package: TSSOP; No of Pins: 16; Temperature Range: Industrial

Manufacturers <u>Analog Devices, Inc</u>

Package/Case TSSOP-16

Product Type Interface - Switches, Multiplexers, Demultiplexers

RoHS Rohs



Images are for reference only

Please submit RFQ for ADG609BRUZ or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

The ADG609 is designed on an enhanced LC2 MOS process which provides low power dissipation yet gives high switching speed and low on resistance. Each channel conducts equally well in both directions when ON and has an input signal range which extends to the supplies. In the OFF condition, signal levels up to the supplies are blocked. All channels exhibit break before make switching action preventing momentary shorting when switching channels. Inherent in the design is low charge injection for minimum transients when switching the digital inputs.

Features

Lifecycle

VSS to VDD Analog Signal Range

Low On-Resistance (30 O max)

Fast Switching Timeston 75 ns maxtoff 45 ns max

Low Power Dissipation (1.5 µW max)

Break-Before-Make Switching Action

ESD > 5000V as per Military

Standard 3015.7

TTL/CMOS Compatible

16-Lead DIP/SOIC/TSSOP Packages

Related Products



ADV7181CBSTZ

Analog Devices, Inc
LQFP-64



AD724JR
Analog Devices, Inc
SOIC-16



ADV7391WBCPZ
Analog Devices, Inc
LFSCP-3



ADV7341BSTZ

Analog Devices, Inc
LQFP-64



Analog Devices, Inc SOP8



ADV7393BCPZ
Analog Devices, Inc
LFCSP-VQ-40



Analog Devices, Inc QFN32



Analog Devices, Inc SOIC-16