

Monolithic 16-Bit Serial/Byte DACPORT; Package: SOIC - Wide; No of Pins: 24;
Temperature Range: Industrial

Manufacturers	Analog Devices, Inc
Package/Case	SOIC-24
Product Type	Data Conversion ICs
RoHS	Pb-free Halide free
Lifecycle	



Images are for reference only

Please submit RFQ for AD660ARZ or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

The AD660 DACPORT® is a complete 16-bit monolithic digital-to-analog converter with an on-board voltage reference, double-buffered latches, and an output amplifier. It is manufactured on the Analog Devices, Inc., BiMOS II process. This process allows the fabrication of low power CMOS logic functions on the same chip as high precision bipolar linear circuitry.

The AD660 architecture ensures 15-bit monotonicity over time and temperature. Integral and differential nonlinearity is maintained at $\pm 0.003\%$ maximum. The on-chip output amplifier provides a voltage output settling time of $10 \mu\text{s}$ to within $\frac{1}{2}$ LSB for a full-scale step.

The AD660 has an extremely flexible digital interface. Data can be loaded into the AD660 in serial mode or as two 8-bit bytes. This is made possible by two digital input pins that have dual functions. The serial mode input format is pin selectable to be MSB or LSB first. The serial output pin allows the user to daisy-chain several AD660 devices by shifting the data through the input latch into the next DAC, thus minimizing the number of control lines required to SIN, CS and LDAC. The byte mode input format is also flexible in that the high byte or low byte data can be loaded first. The double buffered latch structure eliminates data skew errors and provides for simultaneous updating of DACs in a multiDAC system.

The AD660 is available in five grades. AN and BN versions are specified from -40°C to $+85^{\circ}\text{C}$ and are packaged in a 24-lead 300 mil plastic DIP. AR and BR versions are also specified from -40°C to $+85^{\circ}\text{C}$ and are packaged in a 24-lead SOIC. The SQ version is packaged in a 24-lead 300 mil CERDIP package and is also available compliant to MIL-STD-883. Refer to the AD660SQ/883B military data sheet for specifications and test conditions.

Product Highlights

The AD660 is a complete 16-bit DAC, with a voltage reference, double-buffered latches, and an output amplifier on a single chip.

The internal buried Zener reference is laser trimmed to 10.000 V with a $\pm 0.1\%$ maximum error and a temperature drift performance of ± 15 ppm/ $^{\circ}\text{C}$. The reference is available for external applications.

The output range of the AD660 is pin programmable and can be set to provide a unipolar output range of 0 V to 10 V or a bipolar output range of -10 V to $+10$ V. No external components are required.

~~The AD660 is available and its specified DC specifications include ± 1 LSB DNL and ± 1 LSB DNL error. AC specifications include 0.003% THD~~

+ N and 83 dB SNR.

The double-buffered latches on the AD660 eliminate data skew errors and allow simultaneous updating of DACs in multi-DAC applications.

The clear function can asynchronously set the output to 0 V regardless of whether the DAC is in unipolar or bipolar mode.

The output amplifier settles within 10 μ s to $\pm 1/2$ LSB for a full-scale step and within 2.5 μ s for a 1 LSB step over temperature. The output glitch is typically 15 nV-s when a full-scale step is loaded.

Data Sheet, Rev. B, 6/08

Features

Complete 16-Bit D/A Function On-Chip Output Amplifier On-Chip Buried Zener Voltage Reference

15-Bit Monotonic over Temperature

Microprocessor Compatible Serial or Byte Input Double Buffered Latches Fast (40 ns) Write Pulse

Asynchronous Clear (to 0 V) Function

Serial Output Pin Facilitates Daisy Chaining

Unipolar or Bipolar Output

Low Glitch: 15 nV-s

Low THD+N: 0.009%

Related Products




[ADAS3022BCPZ](#)

Analog Devices, Inc
LFCSP-40




[AD574AJNZ](#)

Analog Devices, Inc
PDIP-28




[AD7938BSUZ](#)

Analog Devices, Inc
TQFP-32



[AD7124-8BCPZ-RL7](#)

Analog Devices, Inc
LFCSP-32




[AD7266BSUZ](#)

Analog Devices, Inc
TQPF-32



[AD7401YRWZ](#)

Analog Devices, Inc
SOIC-16



[AD7192BRUZ-REEL](#)

Analog Devices, Inc
TSSOP-24



[AD9680BCPZ-500](#)

Analog Devices, Inc
LFCSP-64