

Line Transceiver 1TR 1TX 1RX 8-Pin SOIC N

Manufacturers	<a href="#">Analog Devices, Inc</a>
Package/Case	SOP-8
Product Type	Interface ICs
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for MAX3483ESA or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

## General Description

MAX3483ESA is a low-power transceiver for RS-485 and RS-422 communication protocols. It is a part of the MAX3483 family of transceivers manufactured by Maxim Integrated.

## Features

- It operates with a single 3.3V or 5V power supply.
- It has a low quiescent current of 375uA.
- It supports data rates up to 250kbps.
- It has a 1/8-unit load option for up to 256 devices on the bus.
- It has a thermal shutdown feature to protect against excessive power dissipation.

## Application

- MAX3483EPA
- MAX3483CPA
- MAX3483CSA
- MAX3483CUE
- MAX3483ECSA



**Related Products**




[MAX3232EEUE](#)

Analog Devices, Inc  
TSSOP-16



[MAX4544EUT+T](#)

Analog Devices, Inc  
SOT-23-6



[MAX202CSE](#)

Analog Devices, Inc  
SOP-16



[MAX485ECPA](#)

Analog Devices, Inc  
DIP-8



[MAX3221EEUE](#)

Analog Devices, Inc  
TSSOP-16



[MAX3232EEUE](#)

Analog Devices, Inc  
TSSOP-16



[MAX490MJA](#)

Analog Devices, Inc  
CDIP-8



[MAX3232EUE](#)

Analog Devices, Inc  
TSSOP-16