

MCP4912-E/SL

Data Sheet

Digital to Analogue Converter, Dual, 10 bit, SPI, 2.7V to 5.5V, SOIC, 14 Pins

Manufacturers <u>Microchip Technology, Inc</u>

Package/Case SOIC-14

Product Type Data Conversion ICs

RoHS Rohs

Lifecycle

Please submit RFQ for MCP4912-E/SL or Email to us; sales@ovaga.com We will contact you in 12 hours.



Images are for reference only

RFO

General Description

MCP4912 is a dual channel, 10-bit DAC with an external voltage reference and SPI interface. It offers high accuracy and low power consumption and is available in various packages. The MCP4912 device is a part of the MCP4902/MCP4912/MCP4922 product family, which are dual channel 8-bit/10-bit/12-bit DACs which use external voltage reference (VREF). These devices provide very high accuracy and low noise performance, and are suitable for consumer and industrial applications, such as set point control, offset adjustment and sensor calibration applications. The low power consumption and small package options make these devices very attractive for many portable and battery-powered applications. If one output is needed then the MCP4901/4911/4921 single channel product family can be used.

Features

10-bit Resolution

Dual Channel Voltage Output

2.7V to 5.5V Operation

Operating Current 350µA (typ)

External Voltage Reference Pin

 $INL \pm 0.5 LSB (typ)$

DNL ± 0.5 LSB (max)

Output Settling Time 4.5 µs

SPI Interface

14-pin PDIP, SOIC, and TSSOP packages

Temperature Range -40°C to +125°C

AEC-Q100 Grade 1 qualified

Related Products



MCP4706A0T-E/CH

Microchip Technology, Inc SOT-23-6



MCP4922-E/SL

Microchip Technology, Inc SOIC-14



MCP4716A0T-E/MAY

Microchip Technology, Inc DFN-6



MCP3564RT-E/ST

Microchip Technology, Inc TSSOP-20



MCP3903-I/SS

Microchip Technology, Inc SSOP-28



MCP48CVB21-E/UN

Microchip Technology, Inc 10-TFSOP, 10-MSOP (0.118, 3.00mm Width)



MCP4728A1T-E/UN

Microchip Technology, Inc DFN-10



MCP3204-CI/ST

Microchip Technology, Inc TSSOP-14