

+/-15kV ESD Protected, 3.3V, Full Fail-safe, Low Power, High Speed or Slew Rate Limited, RS-485/RS-422 Transceivers

Manufacturers	<a href="#">Renesas Technology Corp</a>
Package/Case	8SOIC
Product Type	Interface ICs
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for ISL83071EIBZA or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

## General Description

The Intersil ISL8307XE are BiCMOS 3.3V powered, single transceivers that meet both the RS-485 and RS-422 standards for balanced communication. These devices have very low bus currents (+125mA/-100mA), so they present a true “1/8 unit load” to the RS-485 bus. This allows up to 256 transceivers on the network without violating the RS-485 specification’s 32 unit load maximum, and without using repeaters. For example, in a remote utility meter reading system, individual meter readings are routed to a concentrator via an RS-485 network, so the high allowed node count minimizes the number of repeaters required. Receiver (Rx) inputs feature a “Full Fail-Safe” design, which ensures a logic high Rx output if Rx inputs are floating, shorted, or terminated but undriven. Hot Plug circuitry ensures that the Tx and Rx outputs remain in a high impedance state while the power supply stabilizes. The ISL83070E through ISL83075E utilize slew rate limited drivers which reduce EMI, and minimize reflections from improperly terminated transmission lines, or unterminated stubs in multidrop and multipoint applications. Slew rate limited versions also include receiver input filtering to enhance noise immunity in the presence of slow input signals. The ISL83070E, ISL83071E, ISL83073E, ISL83076E, ISL83077E are configured for full duplex (separate Rx input and Tx output pins) applications. The half duplex versions multiplex the Rx inputs and Tx outputs to allow transceivers with output disable functions in 8 lead packages.

## Features

Pb-Free (RoHS Compliant)

RS-485 I/O Pin ESD Protection:  $\pm 15\text{kV}$  HBM

Class 3 ESD Level on all Other Pins:  $>7\text{kV}$  HBM

Full Fail-safe (Open, Short, Terminated/Floating) Receivers

Hot Plug - Tx and Rx Outputs Remain Three-state During Power-up (Only Versions with Output Enable Pins)

True 1/8 Unit Load Allows up to 256 Devices on the Bus

Single 3.3V Supply

High Data Rates: up to 20Mbps

Low Quiescent Supply Current:  $800\mu\text{A}$  (Max)

Ultra Low Shutdown Supply Current:  $10\text{nA}$

$-7\text{V}$  to  $+12\text{V}$  Common Mode Input/Output Voltage Range

Half and Full Duplex Pinouts

Three State Rx and Tx Outputs Available

Current Limiting and Thermal Shutdown for driver Overload Protection

Tiny MSOP package offering saves 50% board space

## Related Products



### [ISL83491IBZ](#)

Renesas Technology Corp  
SOIC-14



### [ISL3170EIUZ](#)

Renesas Technology Corp  
MSOP-10



### [ISL99227FRZ-T](#)

Renesas Technology Corp  
32-PowerWFQFN



### [ISL83078EIBZA](#)

Renesas Technology Corp  
SOIC-8



### [ISL83072EIBZA](#)

Renesas Technology Corp  
SOIC-8



### [ISL81487EIBZ](#)

Renesas Technology Corp  
SOP-8



[IS82C55AZ](#)

Renesas Technology Corp

PLCC-44



[ISL83387EIVZ](#)

Renesas Technology Corp

TSSOP-24