

RS-422/RS-485 Interface IC RS-485/RS-422 Transceiver

Manufacturers	<a href="#">Analog Devices, Inc</a>
Package/Case	DIP-14
Product Type	Interface ICs
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for MAX491CPD or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

## General Description

MAX491CPD is a specific model of a high-speed, low-power RS-485/RS-422 transceiver integrated circuit (IC) produced by Maxim Integrated.

## Features

- It has a high data rate capability of up to 20Mbps.
- It operates on a low supply voltage range of 4.75V to 5.25V.
- It has a low current consumption of 1.5mA.
- It can operate over a wide temperature range of -40°C to +85°C.
- It has a shutdown mode that reduces power consumption to less than 1µA.

## Application

- Industrial automation and control systems
- Networking equipment
- Medical instrumentation
- Security and surveillance systems
- Telecommunication systems



### Related Products




[MAX3232EEUE](#)

Analog Devices, Inc  
TSSOP-16



[MAX4544EUT+T](#)

Analog Devices, Inc  
SOT-23-6



[MAX202CSE](#)

Analog Devices, Inc  
SOP-16



[MAX485ECPA](#)

Analog Devices, Inc  
DIP-8



[MAX3221EEUE](#)

Analog Devices, Inc  
TSSOP-16



[MAX3223EEUE](#)

Analog Devices, Inc  
TSSOP-16



[MAX490MJA](#)

Analog Devices, Inc  
CDIP-8



[MAX3232EUE](#)

Analog Devices, Inc  
TSSOP-16