

AT28C256-15DM/883

Data Sheet

EEPROM 256K 11MIL GRIND - 150NS

Manufacturers <u>Microchip Technology, Inc</u>

Package/Case CERDIP-28

Product Type Memory

Lifecycle

RoHS



Images are for reference only

Please submit RFQ for AT28C256-15DM/883 or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

The Microchip AT28C256 is a high-performance256Kbit Parallel EEPROM available in both Industrial and Military temp ranges, offeringaccess times to 150ns with power dissipation of 440mW. Deselected, CMOS standbycurrent is less than 200µA. Accessedlike static RAM for the read or write cycle without external components, it contains a 64-byte page register to allow writing of up to 64bytessimultaneously. Features an internal ErrorCorrection Circuit for extended endurance and improved data retention, inMilitary version. Optional Software DataProtection mechanism guards against inadvertent writes; and an extra 64bytes of EEPROM enables device identification or tracking.

The AT28C256 is also available DUAL MARKED where applicable with the appropriate Standard Military Drawing Number - 5962-88525xxxx. See the datasheet for exact MIL product availability.

Features

32 Kbits x 8 (256 Kbit)

 $5V \pm 10\%$ Supply

Parallel Interface

AT28C256E - High Endurance 100K Write Cycles Option

AT28C256F - 3 ms Fast Write Option

150ns access time

Self-Timed Erase and Write Cycles (10 ms max)

Page Write and Byte Write

Data Dalling for and of write detection

Available in Green (Pb/Halide-free) Packaging Low Power Consumption Read / Write current 40 mA (Max) 32-lead, Plastic J-leaded Chip Carrier (PLCC) Standby current TTL 2 mA (Max), CMOS 200 µA (Max) Write-Protection Hardware Protection Software Data Protect Data retention > 10 years Temperature Ranges Standard Temperature Range: -40°C to 85°C Military Temperature Range: -55°C to 125°C 28-lead, 0.600" Wide, Plastic Dual Inline Package (PDIP) 28-lead, 0.300" Wide, Plastic Gull Wing Small Outline (SOIC) 28-lead, Plastic Thin Small Outline Package (TSOP) Available in SMD Dual marked (5962-88525xxxx) CERAMIC Hermetic Packaging 28-Lead, 0.600" Wide, Non-Windowed, Ceramic Dual Inline (Cerdip) 28-Lead, Non-Windowed, Ceramic Bottom-Brazed Flat Package (Flatpack) 32-Pad, Non-windowed, Ceramic, Leadless Chip Carrier (LCC)



AT280256 15DM/883 201247

Related Products



AT27C010-45JU

Microchip Technology, Inc
PLCC-32



Microchip Technology, Inc SOIC-8

AT24CM02-SSHM-B



AT24CM02-SSHD-B
Microchip Technology, Inc
SOIC-8



24LC32AT-I/SN Microchip Technology, Inc SOIC-8



AT28BV256-20SU

Microchip Technology, Inc
SOIC-28



AT24C512C-SSHM-T
Microchip Technology, Inc
SOIC-8



AT24C04D-MAHM-T
Microchip Technology, Inc
UDFN-8



AT28C010E-12DM/883 Microchip Technology, Inc CERDIP-32