

24LC128T-I/MNY

Data Sheet

EEPROM Serial-I2C 128K-bit 16K x 8 3.3V/5V 8-Pin TDFN EP T/R

Manufacturers	Microchip Technology, Inc	
Package/Case	TDFN-8	- Contraction
Product Type	Memory	C.
RoHS	Rohs	
Lifecycle		Images are for reference only

Please submit RFQ for 24LC128T-I/MNY or Email to us: sales@ovaga.com We will contact you in 12 hours.

<u>RFO</u>

General Description

The Microchip Technology Inc. 24AA128/24LC128/24FC128 (24XX128*) is a 16K x 8 (128 Kbit) SerialElectrically Erasable PROM (EEPROM), capable of operation across a broad voltage range (1.7V to 5.5V). It has been developed for advanced, low-powerapplications such as personal communications or dataacquisition. This device also has a page write capability of up to 64 bytes of data. This device is capable of both random and sequential reads up to the 128K boundary. Functional address lines allow up to eightdevices on the same bus, for up to 1 Mbit addressspace. This device is available in the standard 8-pinplastic DIP, SOIC (3.90 mm and 5.28 mm), TSSOP, MSOP, DFN, and Chip Scale packages.

Related Products



AT24CM02-SSHM-B

Microchip Technology, Inc SOIC-8

24FC512-I/SM Microchip Technology, Inc SOIJ-8





AT24CM02-SSHD-B

Microchip Technology, Inc SOIC-8

24AA512-I/SM

Microchip Technology, Inc SOIJ-8



AT24C512C-SSHM-T

Microchip Technology, Inc SOIC-8



24LC256-I/ST

Microchip Technology, Inc TSSOP-8



24LC32AT-I/SN

Microchip Technology, Inc SOIC-8



AT24C04D-MAHM-T

Microchip Technology, Inc UDFN-8